

KEL 24-2MT

Extended Cable Entry Frames



IP54



V2A anti-corrosive
Also available with stainless steel screws (V2A).



Also available with threaded steel bushings.

1

Description	Type	Order No.	Grommets small large	PU
-------------	------	-----------	---------------------------	----

Product Description

The KEL 24-2MT is our largest frame providing the ability to route and seal up to 120 cables.

The cable entry frames KEL 24-2MT series are KEL frames extended with two additional middle frames for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 120 cables. A flat rubber gasket is included in the shipment.

Advantages & Benefits


- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications


Material	Polyamide (PA)
Flame class	UL94-Vo
IP Rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
Temperature	- 40°C to + 140°C (static) - 40°F to + 284°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	126 × 112 mm / Page 192 - 193
Frame depth	17 mm

Accessories


Cable grommets	44 - 48
KEL-EMC Grounding mounts	122 - 124




KEL 24| 30-2 MT 42234 30|- 1




KEL 24| 30-2 MT with V2A screws 42234.200 30|- 1




KEL 24| 27-2 MT 42233 26|1 1




KEL 24| 27-2 MT with V2A screws 42233.200 26|1 1




KEL 24| 24-2 MT 42227 22|2 1




KEL 24| 24-2 MT with V2A screws 42227.200 22|2 1



KEL 24| 21-2 MT 42226 18|3 1



KEL 24| 21-2 MT with V2A screws 42226.200 18|3 1



KEL 24| 12-2 MT 42223 6|6 1



KEL 24| 12-2 MT with V2A screws 42223.200 6|6 1