

# KEL-QTA

## Split Cable Entry Plates



IP54



1

### Product Description

The KEL-QTA easily routes pre-terminated cables, multi-conductors, hoses or conduits without using any tools for assembly.

### Advantages & Benefits






- Quick assembly without tools
- High cable density by using multi-position grommets
- Simple assembly and disassembly in case of change or service
- Routing of cables with and without connectors in a high density
- Suitable for standard industrial connector cut-outs

### Specifications

Material	Elastomer
Flame class	UL94-V0
IP Rating	IP54, with correct selection of the cable grommets QT
Temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Frame depth	17 mm
Type A:	For wall thickness 1.5 - 2.5 mm
Type B:	For wall thickness 2.8 - 4 mm

### Accessories

QT Cable grommets	56
ST-B Plugs	76
FP Flange plates	152 - 157

Description	Type	Order No. Type A	Order No. Type B	Cut-out [mm]	Cables	PU
	KEL-QTA 24 2 -DP 18	43642	43643	112 × 36	pre-terminated 2× 3 - 15 mm without connector 16× max. 7 mm 1× max. 12 mm 1× max. 16 mm	10
	KEL-QTA 24 4	43644	43645	112 × 36	pre-terminated 4× 3 - 15 mm	10
	KEL-QTA 10 1 -DP 18	43655	43658	65 × 36	pre-terminated 1× 3 - 15 mm without connector 18× max. 5 mm	10
	KEL-QTA 10 2 -DP 6	43656	43659	65 × 36	pre-terminated 2× 3 - 15 mm without connector 6× max. 5 mm	10
	KEL-QTA-B4	43660	-	46 × 46	pre-terminated 4× 3 - 15 mm	