







Type	Order No.	Order No.	Cut-out [mm]	Cables		PU	Description
	Type A	Type B		pre-terminated	non-pre-term.		

KEL-QTA 32	43632	43636	∅ 32	1x 3 - 15 mm	-	10	
KEL-QTA 50	43622	43626	∅ 50	2x 3 - 15 mm	-	10	
KEL-QTE 20 2.5	43412	-	∅ 20	1x 2.6 - 3.2 mm	1x max. 5.2 mm	10	
KEL-QTE 20 3	43413	-	∅ 20	1x 3.1 - 3.8 mm	1x max. 5.2 mm	10	
KEL-QTE 20 4	43414	-	∅ 20	1x 3.8 - 4.8 mm	1x max. 5.2 mm	10	
KEL-QTE 20 5	43415	-	∅ 20	1x 4.7 - 5.6 mm	1x max. 5.2 mm	10	

## Product Description

The KEL-QTA easily routes pre-terminated cables, multi-conductors, hoses or conduits without using any tools for assembly.

## Advantages & Benefits

- Fast and easy assembly without tools
- Increased cable density by using multi-position grommets
- Simple assembly and disassembly in case of change or service
- Routing of cables with and without connectors in a high density

## Specifications

Material	Elastomer
Flame class	UL94-V0
IP Rating (QTA)	IP54, with correct selection of the cable grommets (QT single)
Temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimension	Metric sizes
Type A:	For wall thickness 1.5 - 2.5 mm
Type B:	For wall thickness 2.8 - 4 mm

## Accessories

QT Cable grommets 56